

# All-in-one POS Terminal



EC-VP-1100

## Features

- All-in-one FANLESS POS System
- 15" Bezel free with Capacitive touch
- Flexible architectures for peripheral  
MSR / VFD / 15" Second display supported
- Colorful plastic cover to lighten business identification
- Hidden cable management for space management



## Specifications

Processor	Intel® Celeron J1900 up to 2.42 Ghz (Optional Intel® i3 Skylake 6100 core 2.3 dual-core)
System Memory	4GB Standard, Maximum 8GB (1 x 204-pin DDR3L)
Storage Device	1 x 2.5" SATA HDD or 60GB SSD
Graphics	Intel HD
Speaker	Internal Speaker 2W x 2
Housing Color	Black with Silver Trim
LCD Display Size	TFT15"- LED
Resolution	1024 X 768
Brightness (Backlight Type)	350 cd/m2 (LED)
Touch Panel	10-point Projected Capacitive touch (Optional single point PCAP)
OS Supported	Windows 7, Windows 8.1, Windows Embedded 8.1 Industry, Windows 10, Windows 10 IOT, POS Ready 7
I/O Interface	3 * COM port 1 * RJ45 Gigabit LAN 1 * RJ11 1 * VGA 4 * USB 1 * 12V DC Input 1 * 12V DC Output
Power Supply	60W(12V/5A) External Power Adaptor
Operating Temperature	-10°C ~ 50°C (14°F ~ 122°F)
Operating Humidity	15 % -- 80 %
Dimensions	Without Base: 350 (W) x 48 (D) x 274 (H) mm, N.W. 3.8 Kg With Base: 350 (W) x 322 (D) x 340 (H) mm, N.W. 4.95 Kg
Packing	435 (W) x 310 (D) x 413 (H) mm, G.W. 6.85 Kg



With 15" Second Display



With 15" A-shape Second Display