

MS7580 Genesis

Area-Imaging Scanner

Honeywell's MS7580 Genesis™, the world's first presentation area-imaging scanner engineered to decode all standard 1D, PDF and 2D codes, provides enhanced productivity and revolutionary imaging technology in an elegant, yet durable design.

The MS7580 is redefining industry standards for imaging solutions. Breakthrough performance and a versatile form factor make this product suitable for environments ranging from manufacturing to healthcare to retail POS.

Patented CodeGate® technology along with an activation button support menu-scanning and other targeted-scanning applications.

Unlike other scanners with multiple on-board interfaces, the MS7580 has four dedicated memory banks—each one capable of storing full configuration settings for RS232, keyboard wedge, USB and 46xx RS485 interfaces.

Automatic cable detection and configuration simplifies migration to a new interface by eliminating the need to scan programming bar codes. Three additional patented technologies augment the MS7580's unmatched feature set:

Shielded LEDs minimize the intense flashing common among other area imagers.

CodeSelect™ allows the MS7580 to capture up to seven bar codes in a single flash and output data in any predetermined order.

TotalFreedom™ expands scanner functionality by allowing formatting, parsing and decoding plug-ins to be loaded directly to the MS7580 instead of the host system.

For more information on the MS7580 Genesis area-imaging scanner, please visit www.honeywell.com/aidc



Features

- **Motion Tolerance:** Aggressively reads bar codes passing by the scan window
- **Multiple On-Board Interfaces:** Reduces overall system cost
- **TotalFreedom:** Expands scanner functionality by allowing image processing, decoding and formatting plug-ins to be loaded directly to the scanner instead of the host system
- **Image Capture:** Improves document management by capturing and storing electronic images, including coupons, personal checks, signatures and damaged packages
- **Mobile Phone Reading:** Excels at scanning coupons and mobile tickets directly from the screen of a mobile device
- **Flexible Licensing Solution:** Meets diverse scanning requirements by offering models with limited decoding capabilities—purchase decoding licenses to enable additional functionality as the need arises
- **CodeSelect:** Scans up to 7 bar codes in a single flash and outputs data in any predetermined order
- **Optional EAS:** Increases efficiency by simultaneously deactivating EAS tags and decoding bar codes

MS7580 Genesis Technical Specifications

Operational

| | |
|------------------------|--|
| Light Source | Visible Red LED 645 nm ± 7.5 nm |
| Visual Indicators | Blue = ready to scan; White = good read |
| Host System Interfaces | USB, RS232, Keyboard Wedge, IBM 46xx (RS485) |
| Auxiliary Ports | EAS with interlock (EAS model) |

Mechanical

| | |
|--------------------|---|
| Dimensions (LxWxH) | 80 mm x 83 mm x 150 mm (3.2" x 3.3" x 5.9") |
| Weight | 340 g (12 oz) |

Electrical

| | |
|---------------------------|--|
| Input Voltage | 12 VDC ± 0.25 V |
| Operating Power (typical) | 2.3 W (192 mA @ 12 V) |
| Standby Power (typical) | 1.7 W (142 mA @ 12 V) |
| DC Transformers | Class 2: 12 VDC @ 1.25 A |
| LED Class | Class 1: IEC60825-1, EN60825-1 |
| EMC | FCC Part 15, ICES-003, EN55022 Class B |

Environmental

| | |
|-----------------------|--|
| Operating Temperature | 0°C to 40°C (32°F to 104°F) |
| Storage Temperature | -40°C to 60°C (-40°F to 140°F) |
| Humidity | 0% to 95% relative humidity, non-condensing |
| Drop | Designed to withstand 1.5 m (5') drops |
| Environmental Sealing | Sealed to resist airborne particulate contaminants |
| Light Levels | 100,000 Lux (9,290 foot-candles) |

Scan Performance

| | |
|-------------------|--|
| Scan Pattern | Area Image (1280 x 768 pixel array) |
| Motion Tolerance | 200 cm/s (78 in/s) for 13 mil UPC at optimal focus |
| Scan Angle | Horizontal: 46°; Vertical: 28° |
| Print Contrast | 20% minimum reflectance difference |
| Pitch, Skew | 70°, 75° |
| Decode Capability | Reads standard 1D, PDF, 2D, Postal and OCR symbologies. Visit www.honeywell.com/aidc/symbologies for details. *Note: Decode capabilities dependent on kit configuration |



Wall mount
MLPN 46-00913

| Typical Performance* | |
|---|------------------------------|
| Narrow Width | Depth of Field |
| 5.2 mil (1D) | 40 mm - 80 mm (1.6" - 3.1") |
| 7.5 mil (1D) | 30 mm - 120 mm (1.2" - 4.7") |
| 10.4 mil (1D) | 20 mm - 140 mm (0.8" - 5.5") |
| 13 mil (1D) | 0 mm - 152 mm (0" - 6.0") |
| 10.0 mil (PDF) | 0 mm - 120 mm (0" - 4.7") |
| 15.0 mil (PDF) | 30 mm - 120 mm (1.2" - 4.7") |
| *Resolution: 1D: 4 mil (0.102 mm) 2D: 7.5 mil (0.19 mm) | |
| *Performance may be impacted by bar code quality and environmental conditions | |

