

LS4278

Cordless handheld scanner

BAR CODE SCANNERS

Cordless freedom improves productivity and protects profitability

Symbol's cordless LS4278 provides superior bar code scanning in a durable future-proof device that delivers an outstanding total cost of ownership. Workers can move within a 50 ft./15 m radius to scan items — and the elimination of hazardous cables creates a safer work environment. From cashiers moving around the register to scan large, heavy items and check for missed items to healthcare workers double checking that the right patient is receiving the right medication, integrated Bluetooth wireless personal area networking (WPAN) provides reliable and secure wireless transmission of data between the scanner and your host. Productivity is improved, revenues are protected and potential liability due to injury from lifting heavy objects is reduced.

Outstanding scanning performance

The LS4278 is designed to deliver exceptional scanning performance. Users can scan objects at any angle — the innovative multi-line rastering scan pattern eliminates the need for exact aim and positioning of the scanner. The laser line moves vertically during scanning, allowing accurate capture of even the smallest, stacked and poorly printed bar codes on the first scan. And with superior motion tolerance, users no longer need pause between scans, further increasing productivity.

A new level of durability — and a lower TCO

The LS4278 scanner and cradle are designed to withstand all day every day use, from drops to spills, with features that deliver maximum uptime and investment protection. The scanner's patented single board construction eliminates the most common point of failure — the interconnection between multiple boards. Even if the scanner is accidentally dropped, a five-foot (1.5m) drop specification ensures continuous reliable operation. The scanner and cradle offer industrial charging contacts that eliminate wear when cradling the device, providing a reliable charging connection through hundreds of thousands of insertions — other common charging techniques show wear between 5,000 to 10,000 insertions. Drain points are designed into the cradle to protect sensitive internal electronics from accidental liquid spills. Built-in enterprise durability combines with Symbol's services to deliver a low total cost of ownership. Symbol's comprehensive services are available to assist in rapid deployment as well as provide the ongoing support you need to maintain peak performance — and achieve maximum uptime and value.

For more information on the LS4278, contact us at (852) 2836 - 3162 or visit us on the web at: www.manicon.com.



FEATURES

BENEFITS

Bluetooth Class 2 v1.2

(Serial Port & HID Profiles with authentication and security)

Cordless scanning with secure wireless transmission of data

Multi-line rastering scan pattern

Eliminates the need for exact aim and positioning for superior scanning accuracy

Remote scanner management (RSM) ready

Discover, provision and upgrade devices from a central remote location; dramatically reduces management effort and costs

Long life industrial charging contacts

Reliable performance, rated to 250,000+ insertions

Patented, single circuit-board

Lowers TCO by eliminating a major source of vulnerability

Wide working range

Reads good and poor quality bar codes at similar ranges, reducing the need for the user to move the scanner back and forth

Superior motion tolerance

Eliminates the need to pause between scans

Withstands 5 ft./1.5 m drops to concrete

Protects against downtime from breakage due to everyday drops

Powered through host cable

Eliminates need for a power supply; simplifies installation

Plug-and-play; universal cable

Rapid deployment; single cable connects to any computing environment

Multi point-to-point

Use up to three scanners with a single cradle, reducing capital expenditures and maintenance costs

Batch mode operation

Increases application design flexibility to better meet your specific needs

Vertical or horizontal mounting

Provides versatility to accommodate your unique environment

LS4278 Specifications

Physical Characteristics

| | | |
|-----------------------------|---|---|
| Dimensions: | Scanner: 7.3 in. H x 3.85 in. L x 2.7 in. W/ 18.5 cm H x 9.7 cm L x 6.9 cm W Cradle: 2.0 in. H x 8.35 in. L x 3.4 in./ 5 cm H x 21.1 cm L x 8.6 cm W | |
| Weight: | Scanner: ~8.4 oz./238 g; Cradle: ~6.4 oz./183 g | |
| Mounting Options: | Cradle supports vertical or horizontal positions | |
| Voltage & Current: (Cradle) | Voltage | Current (Charging / Non Charging) |
| | 5 +/-10% VDC | 620 mA / 70mA with external power |
| | 5 +/-10% VDC | 450 mA / 70mA with host power through cable |
| | 12 +/-10% VDC | 270 mA / 50mA with external power |
| | 12 +/-10% VDC | 230 mA / 50mA with host power through cable |
| Color: | Cash Register White (shown) or Twilight Black | |

Performance Characteristics

| | |
|-----------------------------|--|
| Light Source: | 650 nm laser diode |
| Scan Element Frequency: | 50Hz |
| Decode Rate: | 200 decodes per second |
| Radio Range: | Minimum 33 ft./10 m; typical warehouse environment 50 ft./15 m |
| Battery Specifications: | 720mAh NiMH - (3) AAA Number of scans per full charge: 32,000+ @ 1 scan/second Charge time: Fully discharged battery: < 3 hours via external power / ~4.5 hours via host power through cable Note: Typical daily scans are less than 4,000, which fully charges within 1 hour |
| Roll / Pitch / Yaw: | +/- 35° / 60° / 60° |
| Nominal Working Distance: | 5 mil (Code 39): 1.5 to 5.5 in. (3.81 to 13.97 cm) 13 mil (100% UPC/EAN): 0 to 19 in. (0 to 48.25 cm) 10 mil (Code 39): 0 to 14 in. (0 to 35.56 cm) 20 mil (Code 39): 0 to 29 in. (0 to 73.66 cm) |
| Print Contrast: | 25% minimum reflectance |
| Multi-Line Aiming Coverage: | At 5 in./12.7 cm reading distance: ~ 0.5 in./1.3 cm At 10 in./25.4 cm reading distance: ~ 1 in./2.5 cm |
| Motion Tolerances: | Horizontal velocity: 200 in./508 cm per second Vertical velocity: 200 in./508 cm per second Angular velocity: 200 in./508 cm per second |

| | |
|--------------------|--|
| Decode Capability: | UPC/EAN and with supplementals, Code 39, Code 39 Full ASCII, Tri-optic Code 39, RSS Variants, UCC/EAN 128, Code 128, Code 128 Full ASCII, Code 93, Codabar (NW1), Interleaved 2 of 5, Discrete 2 of 5 MSI, Codell, IATA, Bookland EAN, Code 32 |
|--------------------|--|

| | |
|-----------------------|---|
| Interfaces Supported: | LS4278 cradle features on-board multiple interface with: RS-232C (Standard, Nixdorf, ICL and Fujitsu); IBM 468x/469x; keyboard wedge; USB (Standard, IBM SurePOS, Macintosh); laser/wand emulation. In addition, Synapse adaptive connectivity allows for connectivity to all of the above plus many non-standard interfaces. |
|-----------------------|---|

User Environment

| | |
|-------------------------|--|
| Operating Temperature: | 32° to 122° F/0° to 50° C |
| Storage Temperature: | -40° to 158° F/-40° to 70° C |
| Humidity: | 5% to 95% non-condensing |
| Drop Specifications: | Withstands multiple 5 ft./1.5 m drops to concrete |
| # of Cradle Insertions: | 250,000+ insertions |
| Ambient Light Immunity: | Immune to normal artificial indoor and natural outdoor (direct sunlight) lighting conditions |

Regulatory

| | |
|--------------------|---|
| Electrical Safety: | UL1950, CSA C22.2 No. 950, EN60950/IEC950 |
| Laser Safety: | CDRH Class II, IEC Class 2 |
| EMI/RFI: | FCC Part 15 Class B, ICES-003 Class B, European Union EMC Directive, Australian SMA |
| Radio: | Bluetooth, Class 2, Version 1.2, Serial Port & HID Profiles 2.402 to 2.480 GHz Adaptive Frequency Hopping (co-existence with 802.11 wireless networks) Data rate: 720 kbps |

Accessories

| | |
|-----------------|--|
| Brackets: | Desktop/wall-mount bracket |
| Power Supplies: | Power supplies are available for applications that do not supply power over the host cable |



LASER LIGHT - DO NOT STARE INTO BEAM - CLASS 2 LASER PRODUCT.
LASERSTRAHLUNG - NICHT IN DEN STRAHL BLICKEN. LASER KLASSE 2.
LUMIÈRE LASER - NE PAS REGARDER DANS LE FAISCEAU. APPAREIL À LASER DE CLASSE 2 630-680nm, 1mW



Manicon Technology Limited

Unit 12, 8/F, New City Centre, Kwun Tong,
Kowloon, Hong Kong

Tel: 2836-3162 Fax: 2836-3093

E-Mail: sales@manicon.com

Web Page: <http://www.manicon.com>

symbol
The Enterprise Mobility Company™