

TM-T70

Thermal Printer

EPSON
EXCEED YOUR VISION




Receipt printer with unique front-facing controls

- Space-saving design ideal for under-counter operations
- Front-facing controls offer total convenience
- Ease-of-use features include drop-in paper load and auto cutter
- 170mm per second print speed for both graphics and text
- High-resolution graphics, text and barcodes for maximum impact
- Flexible interface options offer complete versatility



Thermal Line

TM-T70



Unique design, enhanced service

The first PoS printer with front-facing controls, the TM-T70 is specifically designed for under counter operations in retail and hospitality. With a range of core, user-friendly features including front paper feeding with drop-in paper rolls, auto-cutter, remote maintenance counter and easy access operator covers, the TM-T70 enables fast, easy transactions and enhanced customer service.

Advanced and high-performance

Offering the high quality and reliability of Epson's world renowned TM-T88 series, the TM-T70 has advanced text, graphics and barcode printing capability. Unlike many other printers, the TM-T70 boasts the same quiet, high, print speed of 170 mm/s for both text and graphics.

Robust, reliable, flexible

The compact TM-T70 includes an external rear splash cover for increased spill resistance, enhanced cable management system and full auto status back reporting. The TM-T70 benefits from new drivers including OPoS ADK, Java and Win APD and is equipped with a range of interface options including parallel, serial, USB version 2, powered USB, ethernet and wireless for seamless integration with existing retail systems.



Print method	Thermal line printing
Print font	Font 9 × 17 / 12 × 24
	Column capacity (columns) 56 / 42
	Character size (mm) 0.99 (W) × 2.40 (H) / 1.41 (W) × 3.38 (H)
	Character set 95 Alphanumeric, 48 International, 128 × 11 Graphic
	Bar code: UPC-A, UPC-E, JAN8 (EAN), JAN13 (EAN), CODE39, CODE93, CODE128, ITF, CODABAR
	Two-dimensional code: PDF417, QRCode
	Characters per inch 20.0 cpi / 15.0 cpi
Interfaces	RS-232, Bi-directional parallel Dealer option: RS-485, USB, 10 Base-T I/F
Data buffer	4 KB or 45 bytes
Print speed	Max. 170 mm / sec.
Paper	Dimensions (mm) Roll paper: 79.5 ± 0.5 (W) × dia. 83.0
	Thickness (mm) 0.06 to 0.07
Power	24 VDC ± 7%
Power consumption	Approx. 1.8 A (mean)
D.K.D.function	2 drivers
Reliability	MTBF: 360,000 hours MCBF: 52,000,000 lines
Overall dimensions (mm)	125 (W) × 194 (D) × 114 (H)
Mass (Approx.)	1.8 kg
EMC standards	FCC class A CE marking, AS / NZS CISPR22 class B
Power supply (option)	PS-180
Option	Cable cover
Safety standards	UL / CSA / EN



EPSON
EXCEED YOUR VISION