Epson

TM-U675

Multifunction Printer



- High-speed MICR reading and check printing
- Quietest printer in its class
- Highest reliability rating in its class
- Easy drop-in paper loading and one-touch removal
- Wider throat for smooth drop-in validation
- Superior slip handling with built-in forms stopper
- Optimized features and small footprint perfect for busy teller stations
- One-year warranty

This easy-to-use teller printer offers superior printing quality, validation and slip printing that meets even the most demanding requirements.

In addition, the TM-U675, with its high speed printing, accurate MICR reader and fast check handling, is a perfect match for financial institutions.

All the features you need

Boasting one of the fastest printing speeds in its class, coupled with versatile paper handling, the TM-U675 will help you complete customer transactions in less time. It prints crisp, clean receipts and negotiable items, such as cashier's checks and money orders, at up to 5.14 lines-per-second. It also prints slips and up to 8 lines of validation.

User friendly design

The TM-U675 comes packed with features to streamline your operations. For the handling of documents, the TM-U675 supports 90-degree print rotation and includes a mechanical forms stopper for extra document stability. And its wider throat design enables quick and smooth drop-in validation. It also features an ASB (Automatic Status Back) function to keep operators constantly informed of printer status and a built-in maintenance counter for scheduling routine maintenance.

Outstanding reliability

Designed to withstand the rigors of high transaction environments, the TM-U675, with a MCBF of 37 million lines, delivers the reliability that is critical to keeping your teller lines moving and your customer satisfaction high.

Integration made easy

With Epson's wide range of exclusive Connect-It™ interfaces, including RS-232C, bi-directional parallel, RS-485 and USB, the TM-U675 is compatible with today's best-of-breed and component-based systems and can easily be integrated into your current system.

Backed by the leader

The TM-U675 features the quality and reliability that Epson is known for and is backed by Epson's worldclass service and support programs.



Epson TM-U675 Multifunction Printer

Printer Specifications

General Print method 9-pin, serial impact dot matrix

Print font

Font

Column capacity Receipt: 37 / 50 columns, Slip / Validation: 45 / 60 columns

 $5 \times 9 / 7 \times 9$

Character size $1.56 \times 3.1 \text{mm} (W \times H)/1.24 \times 3.1 \text{mm} (W \times H); \{0.061 \times 0.122^{\circ}/0.049 \times 0.122^{\circ}\}$

Character set 95 Alphanumeric, 37 International, 128 x 11 Graphic characters

Printer Interfaces RS-232C / Bi-directional parallel / RS-485 / USB / Connect-It*

Data buffer 4KB or 45 bytes

Print speed Approx. 5.14 lps (40 columns, 17.8 cpi)

Paper dimensions

Receipts or Journal 82.5 \pm 0.5 x diameter 83mm {3.25 \pm 0.02 x diameter 3.27"} Slip 70 to 148 x 150 to 210mm (W x L) {2.76 to 5.83 x 5.91 to 8.27"} Validation 148 to 150 x 70 to 210mm (W x L) {5.83 to 5.91 x 2.76 to 8.27"}

Paper thickness

Receipts or Journal 0.06 to 0.085mm [0.0024 to 0.0033"]/sheet (total thickness: 0.2mm [0.0079"] or less)

Slip 0.09 to 0.2mm [0.0035 to 0.0079"]/sheet (total thickness: 0.09 to 0.31mm)

[0.0035 to 0.0122"]

Validation 8 lines

Copy capability One original and two copies

Inked ribbon ERC-32 (purple)
Ribbon life 6,000,000 characters
Power supply 24 VDC ± 10%
Power consumption Approx. 1.7 A (mean)

D.K.D. function 2 drivers

Reliability

NV bit image memory

MTBF 180,000 hours MCBF 37,000,000 lines

Overall dimensions $186 \times 298 \times 195 \text{mm} (W \times D \times H) \{7.3 \times 11.7 \times 7.7''\}$

Mass Approx. 4.8 kg {10.6 lbs}

With autocutter approx. 5.8 kg {12.8 lbs} 384 KB can be used to store graphic files

Factory options Autocutter, MICR

Control Board EMI standards VCCI class A, FCC class A, CE marking

Safety standards UL, CSA

Inch values are approximate.

cpi: characters per 25.4mm (characters per inch)

lps: lines per second

*To find out more about our line of Connect-It Interfaces talk to your Epson Sales Representative.

