

HH492

High-Performance Wireless Scanner

Designed for business environment requiring a fast 1D /2D scanning solution with industrial grade durability, HH492 series delivers optimal scanning capabilities on traditional barcodes, digital screens, and damaged or difficult-to-read barcodes.

As Honeywell's new-generation 2D image wireless scanner, HH492 integrates GEN7 platform and 1472 module to decode all standard 1D/2D barcodes. The base allows for data transmission through the BLE module while also charging the device. These key features make the HH492 a valuable asset in inventory management in government departments, distribution centers express delivery outlets, retail, where fast barcode scanning and identification are required.

DESCRIPTION

The Honeywell HH492 makes scanning easier and faster helping users quickly obtain data and minimizing input errors, which allows for increased productivity and simplified workflow.



The robust HH492 has excellent reading performance and can easily read poorly printed and damaged barcodes which helps to reduce the risk of errors and improve operating efficiency.

FEATURES AND BENEFITS



Highly accurate and fast scanning of even damaged and poor-quality barcodes, with an extended scan distance to reach the bottom of the cart without bending and wasted time at point of sale.



Excellent flexibility and commonality for different customer requirements and various application scenarios. Enhanced scanning performance, including product codes, digital codes, screen codes, government and hotel industry data matrixes and dot matrix codes.



A longer Bluetooth® range compared to competitive devices enables greater operational flexibility for line busting or peak season satellite POS stations.



Equipped with a USB data cable and full accessories to meet different application scenarios and facilitate the use.

HH492 Wireless Scanner Technical Specifications

MECHANICAL

Dimensions (L x W x H): 64 mm x 166 mm x 84 mm (2.5 in x 6.5 in x 3.3 in)
Charger/Communication Base: 130 mm x 86 mm x 85 mm (5.1 in x 3.4 in x 3.3 in)
Scanner Weight: 190 g (6.7 oz)
Charger/Communication Base: 150 g (5.29 oz)

ENVIRONMENTAL

Operating Temperature:
Scanner:
Charging: 5°C to 40°C (41°F to 104°F)
Non-Charging: -20°C to 50°C (-4°F to 122°F)
Communication Base:
Charging: 5°C to 40°C (41°F to 104°F)
Non-Charging: 0°C to 50°C (32°F to 122°F)
Storage Temperature:
Scanner/Communication Base: -40°C to 60°C (-40°F to 140°F)
Electrostatic Discharge (ESD) (Scanners and Cradles): ±8 kV indirect coupling plane, ±15 kV direct air
Humidity: 0% to 95% relative humidity, non-condensing
Anti-drop Performance:
Scanner: Withstands five drops from 1.5 m (4.9 ft) to concrete floor
Communication Base: Withstands two drops from 1.0 m (3.3 ft) to concrete floor
Environmental Sealing: IP40
Light Levels: 0 to 100,000 lux (9,290 foot-candles)

SYSTEM ARCHITECTURE

Operating Power (Charging): 2.5 W (500mA @ 5V USB input), 5W (1000mA @ 5V Adaptor input)

DEPTH OF FIELD

TYPICAL PERFORMANCE**	STANDARD RANGE (SR)
5 mil Code 39	25 mm to 200 mm (1.0 in to 7.9 in)
13 mil UPC	15 mm to 400 mm (0.6 in to 15.8 in)
6.7 mil PDF417	15 mm to 160 mm (0.6 in to 6.3 in)
10 mil DM	15 mm to 155 mm (0.6 in to 6.1 in)
20 mil QR	5 mm to 300 mm (0.2 in to 11.8 in)

**Performance may be impacted by barcode quality and environmental conditions.

For more information

sps.honeywell.com

Honeywell Safety and Productivity Solutions

855 S Mint St
Charlotte, NC 28202
800-582-4263
www.honeywell.com

Standby Power:
Charger/Communication Base: 0.25 W (50mA @ 5V)
Host System Interfaces: USB, HID

SCAN PERFORMANCE

Scan Pattern: Area Image (1040 x 720 pixel array) CMOS
Minimum Print Contrast: 25%
Motion Tolerance: 25cm/s (9.8in/s) for 13 mil UPC at optimal focus
Resolution: 4 mil (1D); 6.7 mil (2D)
Scan Angle:
Horizontal: 39.2° nominal
Vertical: 27.4° nominal
Roll, Pitch, Skew: ±180°, ±65°, ±65
Barcode Types: Reads standard 1D, PDF, 2D, and DotCode symbologies
Note: Decode capabilities dependent on configuration.

WIRELESS

Radio/Range: 2.4 GHz to 2.5 GHz (ISM Band) Adaptive Frequency Hopping
Bluetooth v5.2 30 m (98 ft) line of sight with Honeywell charger/communication base
Power Options*:
Battery: 2730mAh Li-ion
Number of Scans: Up to 50,000 scans per charge
Expected Duration of Operation: 12 hours
Expected Charge Time: 4 hours
User Indicators: Good Decode LEDs, Rear View LEDs, Beeper (adjustable tone and volume), Charge Status Indicator
* Battery life depends on usage and other factors

For a complete listing of all compliance approvals and certifications, please visit www.honeywell.com/PSScompliance

For a complete listing of all supported barcode symbologies, please visit www.honeywell.com/PSS-symbologies

Bluetooth is a trademark or registered trademark of Bluetooth SIG, Inc.